

LONGi EcoLife

LR7-54HJBB

490~505M (247 W/m^2)

THE **smarter**
AWARD 



High
Efficiency

Leading
Black Module
Efficiency




Anti
Shading

70%
Output Maintained
when Shaded



Class A
Fire Rating

Highest
Fire Safety
Report



High energy yield
Earlier and longer power
generation
More power from limited roof
space



Loading
6000/3600Pa



High
Wind
Resistance



24.7 %
MAX MODULE
EFFICIENCY**0~3%**
POWER
TOLERANCE**1%**
FIRST YEAR
POWER DEGRADATION**0.35 %**
YEAR 2-30
POWER DEGRADATION**BC-CELL**
LOWER OPERATING
TEMPERATURE





Additional Value

30 Year Power Warranty



Mechanical Parameters

Cell Orientation	108 (6×18)
Junction Box	IP68
Output Cable	4mm ² , +400, ~200mm/±12 00mm length can be customized
Glass	Dual glass, 2.0mm coated tempered glass+1.6mm semi-tempered glass
Frame	Black anodized aluminum alloy frame
Weight	23.5
Dimension	1800×1134×30mm
Packaging	36pcs per pallet / 216pcs per 20' GP / 864pcs per 40' HC

**Tolerance:**
Length: ±2mm
Width: ±2mm

Electrical Characteristics

STC : AM1.5 1000W/m² 25°CNOCT : AM1.5 800W/m² 20°C 1m/sTest uncertainty for P_{max} ±3%

Module Type	LR7-54HJBB-490M	LR7-54HJBB-495M	LR7-54HJBB-500M	LR7-54HJBB-505M
Testing Condition	STC	STC	STC	STC
Maximum Power (P _{max} /W)	490.0	495.0	500.0	505.0
Open Circuit Voltage (V _{oc} /V)	41.25	41.35	41.45	41.55
Short Circuit Current (I _{sc} /A)	15.04	15.15	15.26	15.37
Voltage at Maximum Power (V _{mp} /V)	34.07	34.17	34.27	34.37
Current at Maximum Power (I _{mp} /A)	14.38	14.49	14.59	14.69
Module Efficiency(%)	24.0	24.3	24.5	24.7

Electrical characteristics with different rear side power gain

P _{max} /W	V _{oc} /V	I _{sc} /A	V _{mp} /V	I _{mp} /A	P _{max} gain
525.0	41.45	16.02	34.27	15.32	0.05
550.0	41.45	16.78	34.27	16.05	0.1
575.0	41.55	17.54	34.37	16.73	0.15
600.0	41.55	18.31	34.37	17.46	0.2
625.0	41.55	19.07	34.37	18.19	0.25

Operating Parameters

Operational Temperature	-40°C ~ +85°C
Power Output Tolerance	0 ~ 3%
Maximum System Voltage	DC1500V (IEC)
Maximum Series Fuse Rating	30A
Nominal Operating Cell Temperature	45±2°C
Protection Class	Class II
Fire Rating	IEC Class C

Mechanical Loading

Front Side Maximum Static Loading	6000Pa
Rear Side Maximum Static Loading	3600Pa
Hailstone Test	25mm Hailstone at the speed of 23m/s

Temperature Ratings (STC)

Temperature Coefficient of I _{sc}	+0.050%/°C
Temperature Coefficient of V _{oc}	-0.210%/°C
Temperature Coefficient of P _{max}	-0.240%/°C