

## AC SB M 63A 4POL CG 06KV

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)



### General ordering data

Version	Photovoltaics, Switch, Switch disconnecter, 600 V AC, 63 A, 4 pole, Manual switch
Order No.	<a href="#">3103160000</a>
Type	AC SB M 63A 4POL CG 06KV
GTIN (EAN)	4099987148368
Qty.	1 items

## AC SB M 63A 4POL CG 06KV

Weidmüller Interface GmbH & Co. KG  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

## Technical data

## Approvals

Approvals



ROHS Conform

## Dimensions and weights

Depth	121.1 mm	Depth (inches)	4.7677 inch
Height	165 mm	Height (inches)	6.4961 inch
Width	140 mm	Width (inches)	5.5118 inch
Net weight	768 g		

## Temperatures

Ambient temperature -25 °C...70 °C

## Environmental Product Compliance

RoHS Compliance Status Compliant without exemption  
REACH SVHC No SVHC above 0.1 wt%

## Load break switch

Voltage type	AC	Nominal voltage	690 V
Nominal current	63 A	Number of contacts as NC contact	0
Rated mainly active load-breaking current	63 A	Connection type	Screw connection
Short Circuit Interrupt Capability	15 kA	Rated short-circuit making current	1500 A
Rated peak withstand current	15 kA	Number of breaking operation cycles at rated current	1500
Mechanical endurance class	M2 (10000)	Rated take-over current	400 A
Number of contacts as NO contact	4		

## Classifications

ETIM 7.0	EC000216	ETIM 8.0	EC000216
ETIM 9.0	EC004830	ETIM 10.0	EC004830
ECLASS 11.0	27-07-02-03	ECLASS 12.0	27-07-02-03
ECLASS 13.0	27-07-02-03	ECLASS 14.0	27-07-02-03
ECLASS 15.0	27-07-02-03		

**Drawings**

