

FUSE WSFL 10X85 20A 1K5V GPV

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



gPV 10×85 cylindrical fuse cartridges are designed to provide compact, safe and economical protection of photovoltaic modules (field protection) with voltages up to 1,500 DC. They provide protection against both overload and short circuit (gPV class according to the requirements of IEC60269-6 and UL248-19 standards).

Dati generali per l'ordinazione

Versione	Fotovoltaico, Inserto fusibile, 1500 V, 10x85, gPV, 20 A
N. d'ordine	400002610
Tipo	FUSE WSFL 10X85 20A 1K5V GPV
GTIN (EAN)	8430243419635
CPZ	50 Pezzo

FUSE WSFL 10X85 20A 1K5V GPV

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Dati tecnici**Dimensioni e pesi**

Posizione verticale	85 mm	Altezza (pollici)	3,346 inch
Larghezza	10,3 mm	Larghezza (pollici)	0,406 inch
Peso netto	1,94 g		

Elemento fusibile

Collegamento fusibile standard	IEC 60269-6	Corrente	20 A
Tensione DC nominale	1.500 V		

Classificazioni

ETIM 7.0	EC002704	ETIM 8.0	EC002704
ETIM 9.0	EC002704	ECLASS 11.0	27-14-20-02
ECLASS 12.0	27-14-20-02	ECLASS 13.0	27-14-20-02
ECLASS 14.0	27-14-20-02		

Conformità ambientale del prodotto

REACH SVHC	/
Stato conformità RoHS	Conforme senza esenzione

Omologazioni

ROHS	Conforme
------	----------

Download

Dati ingegneristici	CAD data – Advanced Datasheet
Cataloghi	Catalogues in PDF-format